



# Product Specifications

## LF3000



### Lube, Combination

Fleetguard® LF3000 lube combo spin-on filter combines full-flow and by-pass filtration into one single filter developed to meet or exceed engine requirements. This unique arrangement of filtration provides the perfect balance between efficiency and low restriction to oil flow.

[View product on Fleetguard.com](http://Fleetguard.com)

### Specifications

Media Type	StrataPore	Thread Size	2 1/4-12 UNS-2B
Largest OD	4.68 inch	Length	11.88 inch
Gasket Inside Diameter	4.01 inch	Gasket OD	4.68 inch
Hydrostatic Burst Minimum	249.9365 psi	Rated Flow	76 L/m

### Product Comments

Can be used to replace LF670, LF777, LF691 and LF3333. \*\*\* CAUTION\*\*\* : ONLY use Fleetguard filter on Cummins applications; Stratapore Media

### Related Parts

For  
Upgrade, LF9009

<b>Use</b>				
<b>Uses</b>	3835862S	3826334S	3826336S	3826333S
<b>Service</b>	3826335S	3826332S	3305536S	3826359S
<b>Part</b>	3826360S	3826362S		
<b>Uses</b>				
<b>Service</b>	3831773S			
<b>Gasket</b>				
<b>Filter</b>				
<b>Used</b>	3836091S	3827195S	3834123S	
<b>With</b>				
<b>Replaces</b>	LF3639	LF3677		

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved