



Product Specifications

LF516



Lube, Full-Flow Cartridge

Fleetguard® LF516 cartridge oil filter is environmentally friendly and features technology advances to achieve the high flow rates required by today's modern engine designs.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Length	9.66 inch	Largest OD	5.00 inch
Efficiency Test Std	SAE J1858	Pressure Valve	No
Element Collapse/Burst, Min	699.9 kPa	Primary Particle Efficiency	0.95
Rated Flow	86 L/m	Largest End ID	1.48 inch
Gasket Inside Diameter	1.48 inch	Test Specification	SAE J1858

Related Parts

	153516S	257523S	251152S	254028S	181592S
Uses	184387S	173368S	3301954S	184386S	
Service	153528S	3301949S	183342S	257528S	8265S
Part	69751S	3301950S	179599S	194982S	252917S
	116024S	153520S	3301956S	153518S	
Filter Used With	252916S				

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved