



Product Specifications

LF9009



Lube, Combination

Fleetguard® LF9009 lube combo spin-on filter combines full-flow and by-pass filtration into one single filter developed to meet or exceed engine requirements. This unique arrangement of filtration provides the perfect balance between efficiency and low restriction to oil flow.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	2 1/4-12 UNS-2B	Media Type	StrataPore
Largest OD	4.68 inch	Length	11.88 inch
Gasket Inside Diameter	4.01 inch	Gasket OD	4.68 inch
Efficiency Test Std	CECO 10765	Pressure Valve	No
Hydrostatic Burst Minimum	253.74999999999997 psi	Primary Particle Efficiency	0.987
Rated Flow	105 L/m	Test Specification	CECO 10765

Related Parts

For Upgrade, Use	LF14002NN	LF14009NN
Upgrade Of	LF3000	
Is An Exact Match W/Diff Gasket	LF9039	
Filter Used With	3934644S	

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved