

# **Product Specifications**

## LF9080



Lube, Spin-On

View product on Fleetguard.com

### **Specifications**

Thread Size	M95 X 2.5-7H INT	Media Type	Others
Leasth		Largest OD	4.74 inch
Length	11.60 inch	Gasket OD	4.74 inch
Gasket Inside Diameter	4.00 inch	Pressure Valve	No
Hydrostatic Burst Minimum	304.935 psi	, research raine	, , ,
Rated Flow	105 L/m		

#### **Product Comments**

Venturi Combo Filter with Stratapore media

#### **Related Parts**

For Upgrade, Use LF14001NN LF14000NN

Replaced By LF14000NN

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved