



Product Specifications

LF16462



Lube, Spin-On

Fleetguard® LF16462 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Length	10.24 inch	Largest OD	4.33 inch
Gasket OD	4.02 inch	Efficiency Test Std	ISO 4548-12
Pressure Valve	No	Media Type	Cellulose
Hydrostatic Burst Minimum	217.49999999999997 psi	Pressure Valve Opening Pressure	0.1 kPa
Primary Particle Efficiency	0.987	Rated Flow	90 L/m
Gasket Inside Diameter	3.71 inch	Test Specification	ISO 4548-12

Product Comments

100.000km Change Interval

Related Parts

Is European Version Of LF16465

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved