



# Product Specifications

## FF185



### Fuel, Primary Spin-On

Fleetguard® FF185 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

[View product on Fleetguard.com](https://www.fleetguard.com)

## Specifications

Thread Size	1-14 UNS-2B	Gasket Inside Diameter	2.46 inch
Gasket OD	2.83 inch	Length	6.94 inch
Largest OD	3.68 inch	Standpipe	No
Hydrostatic Burst Minimum	300.15 psi	Primary Particle Efficiency	8.6 micron (c) @ 97%
Rated Flow	7.58 L/min		

## Related Parts

**For Upgrade, Use**      FS1214      FF5336

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or

non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved