



Product Specifications

FF5485



Fuel

Fleetguard® FF5485 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Gasket OD	2.76 inch	Largest OD	3.70 inch
Gasket Inside Diameter	2.44 inch	Hydrostatic Burst Minimum	217.49999999999997 psi
Media Type	StrataPore	Rated Flow	4.5 L/min
Length	7.55 in	Primary Particle Efficiency	7 micron (c) @ 98.7%
Thread Size	M20X1.5-6H		

Product Comments

Stratapore Media

Related Parts

For Upgrade, Use	FF5421			
Filter Used With	FH125	SP72260	FH22011	3939739S

Replaces

FF5420

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved