



Product Specifications

FS19732



Fuel/Water Separator

Fleetguard® FS19732 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Media Type	StrataPore	Thread Size	1-14 UNS-2B
Length	7.964 in	Largest OD	3.69 inch
EFFICIENCY, TWA BY SAE J 1985	0.987	EMULSIFIED WATER SEPARATION	95%
FREE WATER SEPARATION	0.95	Standpipe	NO
Gasket Inside Diameter	2.46 inch	Gasket OD	2.83 inch
MICRON RATING BY SAE J 1985	25 micron	Seam OD	3.668 in

Product Comments

Cummins QSB, QSC, QSL engines Stratapore Media

Related Parts

Includes	FH21080 FH21040 FH22264	FH21051 FH21049	FH21101 FH21102	FH21108 FH21045
Uses Service Part	3942834S			
Filter Used With	FH126	3944287S		
Uses Element	FH22239			

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved