



Product Specifications

LF3664



Lube, Spin-On

Fleetguard® LF3664 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	1 1/8-16 UN-2B	Gasket OD	3.95 inch
Gasket Inside Diameter	3.59 inch	Largest OD	4.24 inch
Length	6.63 inch	Hydrostatic Burst Minimum	203.14499999999998 psi
Pressure Valve	Yes	Rated Flow	65.1 L/m

Related Parts

Replaces LF3362

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved