



# Product Specifications

## FF42000



### Fuel, User Friendly Version

[View product on Fleetguard.com](https://www.fleetguard.com)

## Specifications

Largest OD	3.24 inch	Thread Size	M16 X 1.5-6H INT
Length	4.58 inch	Gasket Inside Diameter	2.52 inch
Gasket OD	2.81 inch	Standpipe	NO
Media Type	Cellulose	Hydrostatic Burst Minimum	300.15 psi
Rated Flow	3.84 L/min	Primary Particle Efficiency	17.3 micron (c) @ 96%

## Related Parts

Is User Friendly Version Of	FF5074	FF5052	FF5018	FF5033
Replaces	FF42001			
Replaced By	FF5074	FF5018	FF5033	FF5052

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved