



Product Specifications

FF5461



Fuel

Fleetguard® FF5461 premium spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

[View product on Fleetguard.com](#)

Specifications

Efficiency Test Std	ISO 19438	Hydrostatic Burst Minimum	217.49999999999997 psi
Primary Particle Efficiency	10 micron (c) @ 99.9%	Rated Flow	1.25 L/min
Largest OD	3.05 inch	Length	4.92 in
Gasket OD	2.76 inch	Gasket Inside Diameter	2.44 inch
Thread Size	M16X1.5-6H		

Related Parts

Stratapore Version Of	FF5018
Upgrade Of	FF5052

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor

completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved