

Product Specifications

FF5644



Fuel

Fleetguard® FF5644 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

View product on Fleetguard.com

Specifications

Gasket OD	4.74 inch	Hydrostatic Burst Minimum	449.93499999999995 psi
Primary Particle Efficiency	4 micron (c) @ 98.7%	Rated Flow	12.67 L/min
Largest OD	4.74 inch	Length	10.4 in
Gasket Inside Diameter	4.00 inch	Thread Size	2.25-12 UNF 2B

Product Comments

For Cummins Hi-Horsepower engines

Related Parts

For Upgrade, Use	FF5782NN	FF5782
Replaces	FF5607	FF5634

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved