



Product Specifications

FF5693



Fuel

Fleetguard® FF5693 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Media Type	StrataPore	Thread Size	1 1/4-12 UNS-2B
Length	12.32 inch	Largest OD	4.74 inch
Gasket Inside Diameter	3.89 inch	Gasket OD	4.40 inch
Standpipe	YES	Efficiency Test Std	SAE J905
Hydrostatic Burst Minimum	144.99275 psi	Primary Particle Efficiency	2 micron (c) @ 88%
Rated Flow	31.42 L/min	Length / Overall Height	12.33 inch
Test Specification	SAE J905		

Product Comments

For fuel island filter used with filter head 3963004

Related Parts

Filter Used With 3963004

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved