



Product Specifications

LF16061

Lube



Fleetguard® LF16061 lube combo spin-on filter combines full-flow and by-pass filtration into one single filter developed to meet or exceed engine requirements. This unique arrangement of filtration provides the perfect balance between efficiency and low restriction to oil flow.

[View product on Fleetguard.com](#)

Specifications

Media Type	Cellulose	Efficiency Test Std	ISO 4548-12
Pressure Valve	Yes	Hydrostatic Burst Minimum	284.2 psi
Pressure Valve Opening Pressure	200 kPa	Primary Particle Efficiency	30 micron (c) @ 98.6%
Rated Flow	38 L/m	Gasket Inside Diameter	2.46 inch
Largest OD	3.69 inch	Gasket OD	2.83 inch
Length	6.95 in	Test Specification	ISO 4548-12
Thread Size	1-16 UNF 2B		

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved