

Product Specifications

LF9031



Lube, Combination

Fleetguard® LF9031 lube combo spin-on filter combines full-flow and by-pass filtration into one single filter developed to meet or exceed engine requirements. This unique arrangement of filtration provides the perfect balance between efficiency and low restriction to oil flow.

View product on Fleetguard.com

Specifications

Media Type	StrataPore	Thread Size	M95X2.5-7H
Largest OD	4.67 inch	Length	11.81 inch
Gasket Inside Diameter	3.99 inch	Gasket OD	4.66 inch
Hydrostatic Burst Minimum	304.935 psi	Pressure Valve	No
		Drimory Portiolo	24.6 mioran (a)
Rated Flow	150 L/m	Primary Particle Efficiency	24.6 micron (c) @ 60%

Product Comments

Suitable for Cummins Centinel® applications. Outer gasket: Vamac rubber. Media Type: Stratapore Venturi Combo

Related Parts

Is An Exact Match W/Diff Gasket LF9001

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved