



Product Specifications

LF9540



Lube

Fleetguard® LF9540 lube combo spin-on filter combines full-flow and by-pass filtration into one single filter developed to meet or exceed engine requirements. This unique arrangement of filtration provides the perfect balance between efficiency and low restriction to oil flow.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Media Type	StrataPore	Largest OD	4.74 inch
Length	11.70 inch	Gasket OD	4.74 inch
Efficiency Test Std	ISO 4548-12	Hydrostatic Burst Minimum	599.8504999999999 psi
Primary Particle Efficiency	20 micron (c) @ 98.7%	Rated Flow	166.6 L/m
Gasket Inside Diameter	4.00 inch	Thread Size	M93X0.351-7H

Product Comments

For Full Flow version, use LF17564.

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or

non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved