



Product Specifications



P550715

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	3.23 inch (82 mm)
Thread Size	3/4-16 UN
Length	4.41 inch (112 mm)
Gasket OD	2.60 inch (66 mm)
Gasket ID	2.24 inch (57 mm)
Efficiency 99%	40 micron
Efficiency Test Std	ISO 4572
Anti-Drainback Valve	No
Bypass Valve	Yes

Bypass Valve Setting LR	15 psi (1 bar)
Bypass Valve Setting HR	19 psi (1.3 bar)
Collapse Burst	75 psi (5.2 bar)
Type	Full-Flow
Style	Spin-On
Primary Application	KUBOTA 1542632430

Packaged Dimensions

Packaged Length	3.3 IN
Packaged Width	3.25 IN
Packaged Height	4.5IN
Packaged Weight	0.86 LB
Packaged Volume	0.0279 FT3

Other Information

Country of Origin	Mexico
NMFC Code	069100-09
HTS Code	8421230000
UPC Code	742330043110

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.