



Product Specifications

LF16173



Lube, Spin-On

Fleetguard® LF16173 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Thread Size	M24X1.5-6H	Gasket Inside Diameter	2.44 inch
Gasket OD	2.76 inch	Length	5.62 inch
Largest OD	3.68 inch	Efficiency Test Std	ISO 4548-12
Pressure Valve	Yes	Hydrostatic Burst Minimum	217.49999999999997 psi
Pressure Valve Opening Pressure	160 kPa	Primary Particle Efficiency	40 micron (c) @ 90%
Rated Flow	30 L/m	Test Specification	ISO 4548-12

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.

Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved