



Product Specifications

LF3327



Lube, Cartridge

Fleetguard® LF3327 premium cartridge oil filter is environmentally friendly and features technology advances to achieve the high flow rates required by today's modern engine designs.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Length	10.57 inch	Largest End ID	2.20 inch
Largest OD	4.74 inch	Gasket Inside Diameter	2.52 inch
Efficiency Test Std	ISO 4548-12	Pressure Valve	No
Element Collapse/Burst, Min	400 kPa	Primary Particle Efficiency	47 micron (c) @ 98.7%
Rated Flow	110 L/m	Test Specification	ISO 4548-12

Related Parts

Replaces	LF4053	LF4144
Uses Service Gasket	3324572	

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of

merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved