



# Product Specifications

## LF9667



### Lube, Combination

Fleetguard® LF9667 premium lube combo spin-on filter combines full-flow and by-pass filtration into one single filter developed to meet or exceed engine requirements. This unique arrangement of filtration provides the perfect balance between efficiency and low restriction to oil flow.

[View product on Fleetguard.com](https://www.fleetguard.com)

### Specifications

Media Type	StrataPore	Thread Size	1.125-16 UNF 2B
Largest OD	4.24 inch	Length	10.39 inch
Gasket Inside Diameter	3.56 inch	Gasket OD	3.94 inch
Pressure Valve	No	Hydrostatic Burst Minimum	304.935 psi
Rated Flow	65 L/m	Primary Particle Efficiency	24.6 micron (c) @ 98.7%

### Product Comments

Venturi Combo Filter with Stratapore media

### Related Parts

<b>Upgrade Of</b>	LF3379 LF16101	LF3321	LF667	LF3675	LF3973
-----------------------	-------------------	--------	-------	--------	--------

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved